



XVL 3

P

Advanced Pump-fed floor standing twist Soft Serve Model for Ice Cream, Custard and plant based recipes.



Performance The Carpigiani reputation for the smoothest, creamiest soft serve in the market is proven with this powerful, versatile model. Hopper mixer accommodates any type of mix with high level of solids or water. Each side can independently accommodate different overrun and mixtures with diverse textures such as custard or yogurt one side and Sorbet on the other.



Convenience Hopper mixer easily snaps into place. Audible Signal alerts when refill is needed.



Savings Unique cylinder construction delivers better results using less electricity. Independent cylinders allow one side to be turned off saving power during low season. Water-cooled & Air Cooled versions available.



Safety TEOREMA guarantees facilitated assistance by providing on-line monitoring and diagnosis on a tablet, phone or PC wherever you are.




Hygiene Unique patented heat cleaning cycle option allows for faster and easier cleaning with less water waste. Standby mode maintains safe product temperatures in the freezing cylinder and mix hopper utilizing minimal energy during idle periods.



*Carp Care kit: request it from your dealer to always keep your machine hygienically perfect.

carpigiani.com/us



	WATER		AIR	
Weights	lbs.	kgs.	lbs.	kgs.
Net	683	310	683	310
Crated	749	340	751	341
Volume	cu. ft.	cu. m.	cu. ft.	cu. m.
Volume	50.15	1.42	50.15	1.42
Dimensions	in.	cm.	in.	cm.
Width	20	51	20	51
Depth	34.1	87	37	94
Height	63.3	161	63.3	161
Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Poles (P)	Wires (W)
208-230/60/3 Water	35A	35A	3P, 3W	
208-230/60/3 Air	35A	35A	3P, 3W	

Specifications

Electrical

A dedicated electrical connection is required. Manufactured to be permanently connected. See the Electrical chart for the proper electrical requirements. Consult your local Carpigiani distributor for cord & receptacle specifications as local codes allow.

Beater Motor

1,5 HP + 1,5 HP

Refrigeration System

R404A

Water Cooled

Water inlets and drain connections in the rear 1/2" MPT

Air Cooled *

Minimum clearance: 4" (10 cm) on both side panels and 0" (0 cm) from the rear panel for proper air circulation.

Cylinder Capacity

13.7 + 13.7 quarts (13 + 13 liters)

All specifications mentioned must be considered approximate; Carpigiani reserves the right to modify, without notice, all parts deemed necessary. This unit may be manufactured in other electrical characteristics and may have additional regulatory agency approvals, please consult the local Carpigiani Distributor. Check name plate for exact electrical data. * Room temperature 68°F (20°C).

Bidding Specs

Electrical Volt _____ Hz _____ Ph _____ Neutral Yes No Cooling Air Water

Options _____



738 Gallimore Dairy Road, Suite 113
High Point, NC - 27265
Toll free (800) 648 4389

Dealer



carpigiani.com/us

an Ali Group Company



The Spirit of Excellence